



1. Using a T30 torques bit remove the three clutch slave cylinder bolts. These will not be reused. (FIG 1) ***Do not pull in the clutch lever until this installation is complete***
2. Using a T40 torques bit remove the bolt holding the OEM plastic chain guard to the frame. The bolt and OEM chain guide can be set aside and will not be reused. (FIG 2)
3. Take the EE clutch slave guard and align it with the three mounting holes of the clutch slave cylinder. When doing so, route the gear sensor wire into the grooves of the EE clutch slave cylinder guard. Once this is lined up insert two of the supplied 6x40 bolts into the lower two mounting holes and just thread in finger tight. (FIG 3)
4. Align the small hole end of the supplied knock down bar in-between the EE clutch slave cylinder guard and the OEM clutch slave, then install the supplied 6x40 bolt leaving it finger tight for now. (FIG 4)
5. Now insert the supplied 8x55 bolt into the rear mount point of the knockdown bar. The bolt will go throw the frame, then the supplied spacer, then the supplied chain slider, then the knockdown bar, and thread into the supplied 8mm nut. (FIG 5)
6. This can be tightened with a T40 torques bit and 12mm wrench. Be sure to have the chain slider on an upward angle. (FIG 6)
7. Using a T30 torques bit tighten all three clutch slave cylinder bolts. (FIG 7)
8. Your installation is now complete. Have fun and enjoy the ride!



WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgement in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI Products will void this limited warranty.) EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing as EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and the Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.

PART NUMBER 13-2024

Clutch Slave Cylinder Guard Installation Instructions

